


**FEATURES:**

- ✓ Maximum element length: 2.37 m
- ✓ Cost-effective transportation
- ✓ Easy assembly (no specialized equipment required)
- ✓ Adaptable to various panel sizes
  - Maximum panel width: 1140 mm
  - Maximum panel length: 2280 mm
  - Panel thickness: 30–40 mm
- ✓ Angle adjustment:
  - 25°
  - 30°
  - 35°
- ✓ Wind and snow load capacity:
  - 22 m/s (wind) – 1,2 kN/m<sup>2</sup> (snow) (Light verion)
  - 26 m/s (wind) – 1,6 kN/m<sup>2</sup> (snow) (Strong verion)
  - 28 m/s (wind) – 1,6 kN/m<sup>2</sup> (snow) (U-Strong verion)
- ✓ Construction class: EXC1
- ✓ Corrosion protection for steel components **Magnelis®**
- ✓ **25-year** coating warranty

**NORMY:**

- ✓ **EN 1090-1**
- ✓ **EN 1090-2**
- ✓ **EN 1090-4**
- ✓ **PN-EN 1991-1-3:** Eurokod 1
- ✓ **PN-EN 1991-1-4:** Eurokod 1
- ✓ **PN-EN 1991-1-8:** Eurokod 3
- ✓ **PN-EN 1999-1-1:** Eurokod 9