

R 25-40 230V



Specifications

ETI Code	002462310
Description	R 25-40 230V
Class name	Modular contactor
Function	Modular contactor
Type	AC
Size	4p, 2-modules
Rated Frequency (Hz)	50/60
Number of NO contacts	4
Rated operational current Ie AC-1/AC-7 (A)	25
Rated operational voltage AC (V)	440V
Rated AC control circuit voltage Uc (V)	230V

[Online product page](#)

Other documentation



[Technical data catalogue](#)

[3D Model](#)

[CE declaration](#)

[Eplan file](#)

ETIM international classification

Classification	EC001653
Class name	Installation contactor for distribution board
Number of normally open contacts	4
Type of drive	50/60
Construction size	4p, 2-modules
Rated operating voltage	230...400V
Rated operation current	25A
Rated excitation voltage	230...230V
Voltage type (operating voltage)	AC
Voltage type (excitation voltage)	AC
Number of contacts as normally open contact	4
Max. incandescent lamp load	3000W
Max. load fluorescent lamp	1190VA
Max. load fluorescent lamp (Duo circuit)	2552VA
Max. load fluorescent lamp (parallel compensated)	1360VA
Slider for hand switch	
Number of modular spacings	2
Built-in depth	60mm
Additional equipment possible	1
Degree of protection (IP)	IP20

Dimension drawing

